



POLYCAB INDIA LIMITED

Industrial Cables LP No. 08/2022-23 Dtd : 1st February 2023

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT LEAD FREE (FRLF) / HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLF	GREEN WIRES HR-FRLS-H-LF	FRLF BOX PACKING	GREEN WIRES HR-FRLS-H-LF BOX PACKING
	90 Mtrs.	90 Mtrs.	180 Mtrs.	180 Mtrs.
0.75	1316	1374		
1	1780	1860	3560	3720
1.5	2596	2709	5192	5418
2.5	4085	4270	8170	8540
4	5970	6240	11940	12480
6	8925	9330	17850	18660
10	15695	16405		
16	23220	24265		

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT LEAD FREE (FRLF) / HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE / FLAME RETARDANT LOW SMOKE (FRLS-H) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – HALOGEN FREE FLAME RETARDANT (HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLF POUCH PACKING	GREEN WIRES HR-FRLS-H-LF POUCH PACKING	FRLS-H POUCH PACKING	HFFR POUCH PACKING
	180 Mtrs.	180 Mtrs.	180 Mtrs.	180 Mtrs.
1	3560	3720	3682	3820
1.5	5192	5418	5371	5572
2.5	8170	8540	8455	8785
4	11940	12480	12360	12835
6	17850	18660	18490	19210

ETIRA PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

DATAR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – HALOGEN FREE FLAME RETARDANT (HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)			HFFR	
	90 Mtrs.	90 Mtrs.	90 Mtrs.	
0.75	1208	1244	1410	
1	1576	1623	1910	
1.5	2306	2310	2785	
2.5	3675	3690	4395	
4	5515	5650	6415	
6	8445	8465	9605	

Size wise Coils per Master Box as below

0.75	90 Mtrs.	28		
1	90 Mtrs.	24	180 Mtrs.	12
1.5	90 Mtrs.	16	180 Mtrs.	10
2.5	90 Mtrs.	12	180 Mtrs.	6
4	90 Mtrs.	8	180 Mtrs.	4
6	90 Mtrs.	6	180 Mtrs.	3
10	90 Mtrs.	1		
16	90 Mtrs.	1		

Notes

- The above rates are exclusive of GST which shall be charged extra.
- This Price List is subject to change without notice.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.